## **DECLARATION OF PERFORMANCE**



No. 921163400 59 004

7.	Unique identification code of the product-type: BS-1634
8.	Intended use/es: 4 zones conventional fire alarm control panel for use in fire detection and fire alarm systems installed in buildings.
9.	Manufacturer: Olympia Electronics N. Lakasas – P. Arvanitidis S.A. 72nd klm Old national road Thessaloniki – Katerini, Kolindros, Pieria, Greece P.O. 60061
10.	System/s of AVCP: System 1
11.	Harmonized standard: EN 54-2:1997 +A1:2006 Fire detection and fire alarm systems – Part 2: Control and indicating equipment

equipment

EN 54-4: 1997 +A1:2002 +A2:2006 Fire detection and fire alarm systems - Part 4: Power supply

## 12. Declared performance/s:

		Harmonised technical specification:		
Essential characteristics	Performance	EN 54-2:1997	EN 54-4:1997	
		+A1:2006	+A1:2002 +A2:2006	Comments
Operational reliability	PASS	4 <sup>a</sup> , 5 <sup>a</sup> , 6 <sup>a</sup> , 7 <sup>a</sup> , 8 <sup>a</sup> , 9 <sup>a</sup> , 12 <sup>a</sup> , 13 <sup>a</sup> , 14 <sup>a</sup>	4 <sup>b</sup> , 5 <sup>b</sup> , 6 <sup>b</sup> , 7 <sup>b</sup> , 8 <sup>b</sup>	a, b
Durability of operational reliability: Temperature	PASS			
resistance		15.4	9.5	
Durability of operational reliability: Vibration	PASS			
resistance		15.6, 15.7, 15.15	9.7, 9.8, 9.15	
Durability of operational reliability: Humidity	PASS			
resistance		15.5, 15.14	9.7, 9.8, 9.15	
Durability of operational reliability: Electrical	PASS	1E 0 to 1E 12	9.9 to 9.13	
stability Passages delay (response		15.8 to 15.13	9.9 (0 9.13	
Response delay (response time to fire)	PASS	7.1, 7.7, 7.11, 7.12		а
Performance under fire conditions	PASS	4, 5, 7		a, b
Performance of power supply	PASS		4, 5, 6	b

Comments:

a) The product has been certified with the available options with requirements of the harmonized technical

specification EN 54-2:1997 +A1:2006 which are mentioned below.

7.8 Output to fire alarm devices

7.11 Delays to outputs

b) The product covered by the standards that are mentioned above is assumed to function during the

alarm condition, in an event of fire, before the fire becomes as large as to affect its functioning. There is

therefore no requirement to function when exposed to direct attack from fire.

The performance of the product identified above is in conformity with the set of declared

performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No

305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Elias Tsologiannis, R&D engineer

Eginio, Pieria, Greece 25/1/2018